


| | | | |
|---|--|--|-----------------------------|
|  | PRODUCT TECHNICAL SPECIFICATION | No. | WT-2011/LP-60 |
| | GRANOMA | Edition no. | 10 |
| | | Date <small>(of actualisation)</small> | September 11th, 2025 |

1. INTRODUCTION

1.1 Subject. The subject of this document is an anti-caking agent for fertilizers.

1.2 Range of the WT subject usage. The product is used for protecting granules of fertilizers against solidation and dust raising.

2. LABELLING

2.1 Labelling examples.

GRANOMA

WT-2011/LP-60

3. QUALITY REQUIREMENTS AND TEST METHODS

3.1 Standard parameters and test methods.

Table 1 – Quality requirements valid for each batch of the product:

| Parameters | Unit | GRANOMA Parameter value | Test method |
|---------------------------------|--------------------|-------------------------------------|-------------------------------------|
| 1 | 2 | 3 | 4 |
| a) Congealing point | °C | 55-65 | PN-ISO 2207:2011 ASTM D 938 |
| b) Flash point | °C | min. 200 | PN-EN ISO 2592:2017-10 ASTM D 92 |
| c) Kinematic viscosity at 100°C | mm ² /s | 4 - 15 | PN-EN ISO 3104:2004 |
| d) Density at 15°C | g/cm ³ | Evaluated, indicated in certificate | PN-EN ISO 3675:2004 |

3.2 Sample taking. According to PN-EN ISO 3170:2006.

4. PACKAGING, STORAGE AND TRANSPORTATION

4.1 Packaging. Granoma is stored in the following way:

- liquid loose in heated storage tanks,
- cans of capacity 200l.

The method of packaging and storage is in accordance with the regulations of transportation of petroleum products described in national and international transportation law.

It is admitted to use other kind of packages previously agreed between recipient, producer and carrier, in condition that product is protected well.

On each package should be placed a label with at least following information:

- a) producer name,
- b) address of producer
- c) labelling according to the point 2.,
- d) mass net or volume,
- e) date of production,
- f) control number.

4.2 Storage. The product should be stored in following way:

- liquid state, at a temperature of 60-85 °C, in closed tanks equipped with heating system, protecting the product against moisture and mechanical impurities, away from heat sources. The Shelf Life of a product stored in accordance with the above guidelines is 6 months.

- solid state in closed packages, protecting the product against moisture and mechanical impurities, away from heat sources, at a temperature not exceeding 25 °C, protected from direct sunlight. The Shelf Life of a product stored in accordance with the above guidelines is 12 months.

4.3 Transportation. The product is not classified as dangerous when shipped by all means of transport and is not a subject of the transportation regulations RID/ADR.

5. ADDITIONAL INFORMATION

5.1 Institution preparing WT: Polwax S.A.; Jasło, Poland

5.2 Standards and referenced documents

PN-EN ISO 3170:2006 – Petroleum liquids. Manual sampling.

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 of 16 December 2008. in on classification, labeling and packaging of substances and mixtures, and amending and repealing Directive 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal. EU L 353 / 2 of 31.12.2008).

Other standards related: table 1

Checked:

SZEF BIURA TECHNOLOGII

Mateusz Kłaczek

Head of the Technology Office

Approved:

DYREKTOR OPERACYJNY

Piotr Jędrzejowski

Operation Director