	PRODUCT TECHNICAL SPECIFICATION	No.	WT-2004/LP-07
	Paraffin LUMINA Paraffin LUMINA II	Edition no.	17
		Date (last actualization)	April 11th, 2024

1. INTRODUCTION

- 1.1. Subject.** The subjects of this document are paraffin LUMINA and LUMINA II obtained in contact refining of crude slack waxes.
- 1.2. Range of the WT subject usage.** Paraffin LUMINA and LUMINA II are mainly used to the production of poured candles.

2. LABELLING

2.1. Labelling examples

Parafina LUMINA	WT-2004/LP-07
Parafina LUMINA II	WT-2004/LP-07

3. QUALITY REQUIREMENTS AND TEST METHODS

3.1. Standard parameters and test methods – according to the table 1.

Table 1. Quality requirements valid for each batch of the product.

Parameters	Units	Paraffin parameter value		Test method
		LUMINA	LUMINA II	
a) Congealing point	°C	55,0 – 65,0		PN-ISO 2207:2011 ASTM D 938
b) Kinematic viscosity at 100°C	mm ² /s	5,0 – 8,0		PN-EN ISO 3104:2004
c) Oil content	%(m/m)	max. 8,0	max. 10,0	PN-C-04160:1980 ASTM D 721-97
d) Mechanical impurities and water content	-	not present		PN-C-96115:1974
e) Flash point,(o.c.)	°C	min. 180		PN-EN ISO 2592:2008 ASTM D 92-97
f) Needle penetration at 25°C	1/10 mm	max.68	max.68	PN-C-04161:1982 ASTM D 1321
g) Appearance	-	white homogenous mass		visual
h) Odour *	-	max. 2	-	PN-C-04353:2004 ASTM D 1833-87

* applies to deodorized LUMINA

3.2. Sample taking – according to PN-EN ISO 3170:2006.

4. PACKAGING, STORAGE AND TRANSPORTATION

- 4.1. Packaging.** Paraffin LUMINA and LUMINA II are stored in a following way: liquid paraffin loose in the heated storage tanks,
 granulated paraffin in a polyethylene bags 20 kg on a wooden pallet 600 kg,
 paraffin slabs on a wooden pallet 1000 kg, slabs in cardboard.

The method of packaging and storage is in accordance with the regulations of transportation of petroleum products described in national and international transportation law.

It is admitted to use other kind of packages previously agreed between recipient, producer and carrier, in condition that product is protected well.

On each package should be placed a label with at least following information:

- a) producer name,
- b) address of producer
- c) labelling according to the point 2.,
- d) mass net or volume,
- e) date of production,
- f) control number.

- 4.2. Storage.** Paraffin LUMINA and LUMINA II should be stored in temperature below 25°C, in closed packages in a shaded place protecting against direct access of sun (UV radiation), humidity and mechanical impurities far from the heat radiators. Shelf Life of the product stored in accordance with the above guidelines is 5 years.

- 4.3. Transportation.** The product is not classified as dangerous when shipped by all means of transport and is not a subject of the transportation regulations RID/ADR.

5. ADDITIONAL INFORMATION


- 5.1. Institution preparing WT:** Polwax S.A., Jasło, Poland.

5.2. Standards and referenced documents

PN-EN ISO 3170:2006 Petroleum liquids. Manual sampling.

Other standards related: table 1.

Verified:
SZEF BIURA TECHNOLOGII


Wojciech Szczypka

.....
Head of the Technology Office

Approved:

DYREKTOR OPERACYJNY


Piotr Jodłowski

.....
Operative Director