



Less obvious uses

Paraffin has a very wide range of applications, which means that it can be found in many industries, including in the candle and gravelight industry, furniture, food and automotive industries. However, it also has less obvious applications.

It has found its destiny in the school supplies industry. Waxes, which constitute components for the production of plasticine and wax crayons, are obtained on the basis of paraffin. What is more, wax for plasticine is a product intended for contact with food.



For special purposes

Bituminous mass is a material that is a mixture of aggregates, binders and various types of fillers and is one of the most commonly used components in road construction. Its unique composition allows for efficient repairs of the surface and filling in the defects that occur in it.

The portfolio of our company includes one of the components of bituminous mass – the filler. The developed special mixture of mineral material coated with substances of petroleum origin with the optional addition of activated carbon allows for certain modifications of asphalt mixtures.



PRODUCT	MAIN APPLICATION	TECHNICAL SPECIFICATIONS
WAX FOR CRAYON	Used in the production of crayons	Current Safety Data Sheets and Information Sheets as well as Technical Conditions of individual products are available on our website polwax.pl
WAX FOR PLASTICINE	Used as a component for the production of plasticine. The product may be intended for food contact	
FILLER FOR BITUMINOUS MASSES	Raw material used to modify asphalt mixes used in construction and road building	

Packaging, storage

	WAX FOR CRAYON	WAX FOR PLASTICINE	FILLER FOR BITUMINOUS MASSES
BULK	●	●	●
PASTILLES IN 20 KG POLYETHYLENE BAGS ON 600 KG PALLETS	●	●	●
PANELS IN 24 KG CARTONS ON 720 KG PALLETS	●	●	●
CARTONS APPROX. 20 KG, MAX. 40 CARTONS ON A PALLET	●	●	●
"BIG BAG" PACKAGING			●



FCM/GMP

some products intended for direct contact with food



DEDICATED PURPOSE

products dedicated to specific applications

Product suitability guarantee

The guarantee of suitability of individual products applies only to physical and chemical parameters and is counted from the date of sale. Detailed parameters are specified in the technical conditions available at polwax.pl

Storage method

The products should be stored in closed packages, protected against direct sunlight, moisture and mechanical impurities, away from heat sources. In addition, the technical conditions include information on the appropriate storage temperature, as well as the possible shelf life of individual products stored in accordance with the guidelines.

Conditions of delivery

The products are manufactured in the Production Plant in Jasło (PL38200) and Czechowice-Dziedzice (PL43502). Possible collection by own transport on the basis of the FCA production plant. It is possible to organize transport by Polwax S.A. (based on CPT), after presenting a price offer including delivery costs to the customer's premises.

Orders and delivery schedules

Orders for full truck loads should be sent at least 7 days before the planned shipment of the product. In the case of larger quantities for regular collections, it is advisable to send a monthly collection schedule by the 20th day of the month preceding the month of delivery.