



**For the candle
industry**



Candle industry

Candles are readily available products, made of various types of wax, with various shapes, colours and fragrances.

Paraffin candles were the basic and most common version since the mid-nineteenth century. It was then that crude oil began to be distilled, from which a waxy substance called paraffin was successfully separated.

Paraffin is a mixture of saturated hydrocarbons – solid alkanes, with a different number of carbon atoms in the molecule, the presence of which determines its physical state. It is obtained through the process of refining heavy crude oil fractions. During the production of paraffin candles, pure paraffin is enriched with modifying substances, e.g. stearin, pigments or fragrances.



PRODUCT	MAIN APPLICATION	TECHNICAL SPECIFICATIONS
PARAFFIN LTP STANDARD	Applied mainly in the manufacture of high-quality candle accessories	Current Safety Data Sheets and Information Sheets as well as Technical Conditions of individual products are available on our website polwax.pl
PARAFFIN LTP LOW OIL CONTENT		
PARAFFIN LTP 56/25-G		
PARAFFIN PWX FLEX	Paraffin with increased elasticity for the production of candle accessories, primarily for the production of votive candles	

Raw materials for the production of candles

Waxes for the production of candle products guarantee high quality, and the continuous availability of raw materials allows us to meet the individual needs of our customers.

The range of products constituting the basic raw materials includes paraffins of various physical properties – in particular the solidification point, and the oil content does not exceed 1.1%.

These products, apart from their main application, which is the production of high-quality candle accessories, are also used in the paper, textile, varnishing, wood and chemical industries.

We also offer PWX FLEX – a product used in the production of drawn candles, which are used for ritual purposes in Orthodox churches.*

*Availability and delivery dates are determined on an ongoing basis

Packaging, storage	PARAFFIN LTP STANDARD	PARAFFIN LTP LOW OIL CONTENT	PARAFFIN LTP 56/25-G	PARAFFIN PWX FLEX
BULK (LIQUID) IN HEATED STORAGE TANKS	●	●	●	●
GRANULATE IN 20 KG POLYETHYLENE BAGS ON 600 KG PALLETS	●	●	●	●
PANELS IN 24 KG CARTONS ON 720 KG PALLETS	●	●	●	●
PANELS ON 1000 KG PALLETS	●	●	●	●
PASTILLES IN 20 KG POLYETHYLENE BAGS ON 600 KG PALLETS	●	●	●	
GRANULATE IN POLYETHYLENE BAGS "BIG BAG" 600 KG		●		




STABILITY

oil content not exceeding 1.1%



FCM/GMP

some products intended for direct contact with food



INTENDED USE

used e.g. in the candle-making, paper-making, textile, varnishing and chemical industries



QUALITY

products with a guarantee of high quality

Product suitability guarantee

The guarantee of suitability of individual products applies only to physical and chemical parameters and is counted from the date of sale. Detailed parameters are specified in the technical conditions available at polwax.pl

Storage method

The products should be stored in closed packages, protected against direct sunlight, moisture and mechanical impurities, away from heat sources. In addition, the technical conditions include information on the appropriate storage temperature, as well as the possible shelf life of individual products stored in accordance with the guidelines.

Conditions of delivery

The products are manufactured in the Production Plant in Jasło (PL38200) and Czechowice-Dziedzice (PL43502). Possible collection by own transport on the basis of the FCA production plant. It is possible to organize transport by Polwax S.A. (based on CPT), after presenting a price offer including delivery costs to the customer's premises.

Orders and delivery schedules

Orders for full truck loads should be sent at least 7 days before the planned shipment of the product. In the case of larger quantities for regular collections, it is advisable to send a monthly collection schedule by the 20th day of the month preceding the month of delivery.